



EN 13859-1
Version No 4
September 2016



DECLARATION OF PERFORMANCE
TLX Gold (TLX UV25 Breather membrane)
MFTLXGOLDCPR

1. Unique identification code of the product-type:	TLX Gold
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:	See product
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	BS EN 13859-1:2014 (As per BMTLXUV25CPR) Flexible sheets for waterproofing. Definitions and characteristics of underlays. Underlays for discontinuous roofing BS EN 13859-2:2014 (As per BMTLXUV25CPR) Flexible sheets for waterproofing. Definitions and characteristics of underlays. Underlays for walls
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Web Dynamics Ltd. Moss Lane Blackrod Bolton Lancashire BL5 5JB
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):	Not Relevant
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:	3
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:	BTTG (NB 0338 & 0339) performed ITT under system 3 and issued test reports
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:	Not Relevant



EN 13859-1
Version No 4
September 2016

9. Declared Performance

Essential Characteristics		Performance	
Property	Standard	Nominal	Notified body
Resistance to fire	EN 13501-1	Class E	BTTG
Resistance to water penetration	EN 1928 (A)	W1	BTTG
Water vapour transmission (S_d)	EN ISO 12572 (C)	0.025	BTTG
Tensile properties (MD)	EN 12311-1	420 N/50mm	BTTG
Tensile properties (CD)	EN 12311-1	245 N/50mm	BTTG
Resistance to tearing (MD)	EN 12310-1	294 N	BTTG
Resistance to tearing (CD)	EN 12310-1	224 N	BTTG
Flexibility at low temperature (Pliability)	EN 1109	-40°C	BTTG
Artificial ageing by UV and Heat	EN 1296 and EN 1297	NPD	BTTG
Resistance to water penetration after ageing	EN 1928 (A)	W1	BTTG
Tensile properties after ageing (MD)	EN 12311-1	375 N/50mm	BTTG
Tensile properties after ageing (CD)	EN 12311-1	215 N/50mm	BTTG

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Tim Woodbridge

Managing Director

Bolton, United Kingdom 29/09/2016